

Lubritac

Adhesive Gear Lubricant



Product Data

Description

Lubritac is a highly adhesive gear lubricant specifically designed for the lubrication of Locomotive Traction Motor Gears.

It can be used in modern locomotives and is also fully compatible with older systems such as those found on heritage equipment.

The formation of a tacky adhesive coating on gear surfaces provides excellent water resistance, corrosion protection and wear prevention even under conditions of high stress/load.

Benefits

- Proven Formulation
- Highly Adhesive
- Strong Shock Load Performance
- Excellent Water Resistance
- High Levels of Lubricity
- Free from Heavy Metals

Applications

Lubritac can be used in a wide variety of Railway Locomotive Stock both old and new. Its traditional formulation provides exceptional and reliable performance in even the most severe conditions. Easily applied by brush or by pouring directly into gear casings by pre heating. Very stable formulation, will not dry or flake off.

Physical Properties

Name	Units	Value
Soap/Oil		Bitumen Thickened Mineral Oil
Appearance		Opaque/Shiny
Colour		Black
Viscosity @ 90°C	mm ² /s	500
Pour Point	°C	>15

Packaging

Available in 1 kg, 9 x 1 kg, 12 x 1 kg, 50 kg Kegs, and 180 kg Drums.